

MALLEABLE IRON/HOT DIPPED GALVANIZED ONE-HOLE STRAPS

FOR THREADED RIGID CONDUIT AND IMC

APPLICATION

Click-on type one-hole straps for rigid conduit or IMC. Provides support for the conduits, as required by the National Electrical Code.

FEATURES

- Heavy Duty Casting

STANDARD MATERIALS

Malleable Iron

STANDARD FINISH

Hot Dipped Galvanized/Zinc Plated

OPTIONAL FINISH


For Malleable Iron / Zinc Plated, please remove suffix 'G' from Hot Dipped Galvanized Catalog Number and see page 86.



TYPE 133G



New Product



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
132G	1/2"	1.437	0.625	0.312	100	1000	6	70200
133G	3/4"	1.750	0.750	0.312	100	1000	8	70201
134G	1"	2.125	0.937	0.312	50	500	9	70202
135G	1-1/4"	2.375	1.062	0.437	-	100	22	70203
136G	1-1/2"	2.750	1.062	0.500	-	50	32	70204
137G	2"	3.937	1.250	0.562	-	50	44	70205
138G	2-1/2"	3.937	1.250	0.562	-	25	66	70206
139G	3"	5.187	1.750	0.562	-	10	159	70207
141G	3-1/2"	5.562	2.125	0.750	-	10	185	70208
148G	4"	6.500	2.250	0.750	-	10	221	70209
150G	5"	10.040	2.750	0.750	-	5	369	70210
152G	6"	12.500	3.130	0.750	-	5	631	70211

MALLEABLE IRON/HOT DIPPED GALVANIZED CLAMP BACK SPACERS

FOR THREADED RIGID CONDUIT AND IMC

APPLICATION

Provides space between conduit and mounting surface, for use with malleable iron or aluminum straps.

FEATURES

- Heavy Duty Casting
- Can be used with one hole straps.

STANDARD MATERIALS

Malleable Iron

STANDARD FINISH

Hot Dipped Galvanized/Zinc Plated

OPTIONAL FINISH


For Malleable Iron / Zinc Plated, please remove suffix 'G' from Hot Dipped Galvanized Catalog Number and see page 86.



TYPE 901G



New Product



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	DIM D	UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
900G	1/2"	2.000	1.000	0.500	0.313	100	1000	8	70212
901G	3/4"	2.300	1.060	0.500	0.313	100	500	12	70213
902G	1"	2.320	1.250	0.560	0.375	50	500	16	70214
903G	1-1/4"	3.430	1.870	0.750	0.438	50	250	22	70215
904G	1-1/2"	3.810	1.870	0.810	0.438	-	25	35	70216
905G	2"	4.750	1.920	1.000	0.563	-	25	51	70217
906G	2-1/2"	5.750	2.410	1.000	0.563	-	25	81	70218
907G	3"	6.780	2.620	1.000	0.563	-	25	83	70219
908G	3-1/2"	7.120	2.870	1.060	0.750	-	20	148	70220
909G	4"	8.830	3.060	1.060	0.750	-	10	199	70221
910G	5"	10.125	3.750	1.188	0.750	-	10	344	70222
911G	6"	12.188	4.000	1.500	0.750	-	10	419	70223