

# SPECIFICATION GRADE BRONZE INSULATED GROUNDING BUSHING

FOR THREADED RIGID CONDUIT AND IMC

## APPLICATION

To protect insulated conductors from abrasion during pulling and from mechanical vibration.

To provide voltage gradient between live conductors and ground at point of electrical and mechanical stress on conductor insulation.

## FEATURES

- Molded-on high impact phenolic thermosetting insulation
- UL insulation temperature rating 150°C
- Positive metallic conduit stop
- For Highly corrosive atmospheres

## STANDARD MATERIALS

Bushing: Bronze  
Lug: Copper  
Screws: Stainless Steel

## STANDARD FINISH

Lug: Tin Plated



**TYPE BRLG-1504**

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F	UNIT PACK	MASTER PACK	LBS./100 PCS.	UPC #
<b>BRLG-1504</b>	1-1/2"	1.504	2.315	0.768	1.669	1/4"-28UNF	#10-24UNC	-	25	35	10670
<b>BRLG-2004</b>	2"	2.000	2.752	0.768	1.900	1/4"-28UNF	#10-24UNC	-	25	35	10675
<b>BRLG-3104</b>	3"	3.024	4.031	1.039	2.531	1/4"-28UNF	#10-24UNC	-	10	85	10680