

# MALLEABLE IRON RIGID SET-SCREW CONNECTORS

FOR THREADLESS RIGID CONDUIT AND IMC

## APPLICATION

To connect threadless rigid conduit to boxes and enclosures.

## FEATURES

- Concrete tight
- Available with insulated throat
- Male hub thread (NPS)

## STANDARD MATERIALS


Malleable Iron

## STANDARD FINISH

Zinc Plated



**TYPE TRC-50**




CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
<b>TRC-50</b>	1/2"	1.375	0.438	1.313	25	250	13	70830
<b>TRC-75</b>	3/4"	1.688	0.500	1.563	25	100	21	70831
<b>TRC-100</b>	1"	1.938	0.563	1.875	5	25	38	70832
<b>TRC-125</b>	1-1/4"	2.188	0.625	2.188	5	25	44	70833
<b>TRC-150</b>	1-1/2"	2.313	0.625	2.500	5	20	67	70834
<b>TRC-200</b>	2"	2.438	0.625	2.938	2	10	105	70835
<b>TRC-250</b>	2-1/2"	3.188	0.750	3.625	2	10	190	70836
<b>TRC-300</b>	3"	3.813	0.875	4.250	1	5	272	70837
<b>TRC-350</b>	3-1/2"	4.313	0.938	4.688	1	5	367	70838
<b>TRC-400</b>	4"	4.625	0.938	5.188	1	5	427	70839
<b>TRC-500</b>	5"	4.750	1.375	6.500	-	1	695	70890
<b>TRC-600</b>	6"	4.938	1.500	7.500	-	1	911	70900

**Insulated Throat**



**TYPE TRC-50T**



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
<b>TRC-50T</b>	1/2"	1.375	0.500	1.313	25	250	14	70840
<b>TRC-75T</b>	3/4"	1.688	0.563	1.563	25	100	22	70841
<b>TRC-100T</b>	1"	1.938	0.625	1.875	5	25	39	70842
<b>TRC-125T</b>	1-1/4"	2.188	0.688	2.188	5	25	54	70843
<b>TRC-150T</b>	1-1/2"	2.313	0.688	2.500	5	20	70	70844
<b>TRC-200T</b>	2"	2.438	0.688	2.938	2	10	106	70845
<b>TRC-250T</b>	2-1/2"	3.188	0.813	3.625	2	10	191	70846
<b>TRC-300T</b>	3"	3.813	0.938	4.250	1	5	280	70847
<b>TRC-350T</b>	3-1/2"	4.313	1.000	4.688	1	5	380	70848
<b>TRC-400T</b>	4"	4.500	1.000	5.188	1	5	455	70849
<b>TRC-500T</b>	5"	4.688	1.438	6.500	-	1	701	70170
<b>TRC-600T</b>	6"	4.938	1.563	7.500	-	1	920	70180