

ALUMINUM SET-SCREW CONDUIT BODIES WITH COVER AND GASKET

FOR EMT CONDUIT

APPLICATION

To provide access to conductors for pulling, splicing, and maintenance. Used for thinwall conduit.

FEATURES

- Die cast from high-strength, corrosion and weather resistant, copper-free aluminum alloy.
- Flat back design for easy mounting close to walls.
- Assembled with neoprene gasket and stamped cover.

STANDARD MATERIALS

1/2" - 2"
Die Cast/Copper-Free
Aluminum


2 1/2" - 4"
Sand-Cast Copper-Free
Aluminum

STANDARD FINISH

Aluminum Enameled




TYPE LL1ATCG



| CATALOG NUMBER | TRADE SIZE | DIM A | DIM B | DIM C | MAX WIRE SIZE | VOL. CU.IN. | UNIT PACK | MASTER PACK | LBS. / 100 PCS. | UPC # |
|----------------|------------|-------|-------|-------|---------------|-------------|-----------|-------------|-----------------|-------|
| LL TYPE | | | | | | | | | | |
| LL1ATCG | 1/2" | 4.31 | 2.06 | 1.38 | N/A | 4.35 | 10 | 50 | 25 | 10440 |
| LL2ATCG | 3/4" | 5.06 | 2.25 | 1.63 | 3 #6 AWG | 7.30 | 10 | 50 | 37 | 10441 |
| LL3ATCG | 1" | 5.87 | 2.63 | 1.88 | 3 #4 AWG | 12.20 | 5 | 25 | 45 | 10442 |
| LL4ATCG | 1-1/4" | 7.81 | 3.63 | 2.50 | 3 #2 AWG | 35.80 | - | 10 | 98 | 10443 |
| LL5ATCG | 1-1/2" | 7.81 | 3.63 | 2.50 | 3 #1/0 AWG | 35.80 | - | 10 | 92 | 10444 |
| LL6ATCG | 2" | 10.06 | 4.44 | 3.38 | 3 #4/0 AWG | 69.70 | - | 5 | 245 | 10445 |
| LL7ATCG | 2-1/2" | 12.81 | 5.75 | 4.00 | 3 #300 MCM | 69.70 | - | 1 | 388 | 10446 |
| LL8ATCG | 3" | 12.81 | 5.75 | 4.50 | 3 #350 MCM | 186.00 | - | 1 | 439 | 10447 |
| LL9ATCG | 3-1/2" | 15.62 | 11.69 | 5.63 | 3 #350 MCM | 306.00 | - | 1 | 924 | 10448 |
| LL10ATCG | 4" | 15.62 | 11.69 | 5.63 | 3 #350 MCM | 308.00 | - | 1 | 882 | 10449 |



TYPE LR1ATCG



| CATALOG NUMBER | TRADE SIZE | DIM A | DIM B | DIM C | MAX WIRE SIZE | VOL. CU.IN. | UNIT PACK | MASTER PACK | LBS. / 100 PCS. | UPC # |
|----------------|------------|-------|-------|-------|---------------|-------------|-----------|-------------|-----------------|-------|
| LR TYPE | | | | | | | | | | |
| LR1ATCG | 1/2" | 4.31 | 2.06 | 1.38 | N/A | 4.35 | 10 | 50 | 23 | 10430 |
| LR2ATCG | 3/4" | 5.06 | 2.25 | 1.63 | 3 #6 AWG | 7.30 | 10 | 50 | 38 | 10431 |
| LR3ATCG | 1" | 5.87 | 2.63 | 1.88 | 3 #4 AWG | 12.20 | 5 | 25 | 49 | 10432 |
| LR4ATCG | 1-1/4" | 7.81 | 3.63 | 2.50 | 3 #2 AWG | 35.80 | - | 10 | 98 | 10433 |
| LR5ATCG | 1-1/2" | 7.81 | 3.63 | 2.50 | 3 #1/0 AWG | 35.80 | - | 10 | 94 | 10434 |
| LR6ATCG | 2" | 10.06 | 4.44 | 3.38 | 3 #4/0 AWG | 69.70 | - | 5 | 254 | 10435 |
| LR7ATCG | 2-1/2" | 12.81 | 5.75 | 4.00 | 3 #300 MCM | 69.70 | - | 1 | 366 | 10436 |
| LR8ATCG | 3" | 12.81 | 5.75 | 4.50 | 3 #350 MCM | 186.00 | - | 1 | 406 | 10437 |
| LR9ATCG | 3-1/2" | 15.62 | 11.69 | 5.63 | 3 #350 MCM | 306.00 | - | 1 | 928 | 10438 |
| LR10ATCG | 4" | 15.62 | 11.69 | 5.63 | 3 #350 MCM | 308.00 | - | 1 | 902 | 10439 |