

# ALUMINUM SET-SCREW CONDUIT BODIES WITH COVER AND GASKET

FOR EMT CONDUIT

## APPLICATION

To provide access to conductors for pulling, splicing, and maintenance. Used for thinwall conduit.

## FEATURES

- Die cast from high-strength, corrosion and weather resistant, copper-free aluminum alloy.
- Flat back design for easy mounting close to walls.
- Assembled with neoprene gasket and stamped cover.

## STANDARD MATERIALS

1/2" - 2"  
Die Cast/Copper-Free  
Aluminum

2 1/2" - 4"  
Sand-Cast Copper-Free  
Aluminum

## STANDARD FINISH

Aluminum Enameled



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	MAX WIRE SIZE	VOL. CU.IN.	UNIT PACK	MASTER PACK	LBS./100 PCS.	UPC #
<b>T TYPE</b>										
<b>T1ATCG</b>	1/2"	4.75	2.06	1.38	N/A	4.35	10	50	23	10420
<b>T2ATCG</b>	3/4"	5.56	2.25	1.63	3 #6 AWG	7.25	10	50	38	10421
<b>T3ATCG</b>	1"	6.44	2.63	1.88	3 #4 AWG	12.20	5	25	53	10422
<b>T4ATCG</b>	1-1/4"	8.25	3.56	2.50	3 #2 AWG	33.10	-	10	100	10423
<b>T5ATCG</b>	1-1/2"	8.38	3.56	2.50	3 #1/0 AWG	33.10	-	10	98	10424
<b>T6ATCG</b>	2"	10.69	4.38	3.13	3 #4/0 AWG	67.00	-	5	265	10425
<b>T7ATCG</b>	2-1/2"	13.25	5.75	4.00	3 #4/0 AWG	67.00	-	1	375	10426
<b>T8ATCG</b>	3"	13.25	5.75	4.50	3 #4/0 AWG	175.00	-	1	444	10427
<b>T9ATCG</b>	3-1/2"	16.13	7.69	5.63	3 #400 MCM	298.00	-	1	1146	10428
<b>T10ATCG</b>	4"	16.13	7.69	5.63	3 #400 MCM	300.00	-	1	1079	10429