

EMT STRAPS

FOR EMT CONDUIT

APPLICATION

Click-on type one-hole straps for E.M.T. Provides support for the conduits, as required by the National Electrical Code.

STANDARD MATERIALS


Steel

STANDARD FINISH

Zinc Plated



One-Hole



TYPE 143S

| CATALOG NUMBER | TRADE SIZE | DIM A | DIM B | DIM C | DIM D | UNIT PACK | MASTER PACK | LBS. / 100 PCS. | UPC # |
|----------------|------------|-------|-------|-------|-------|-----------|-------------|-----------------|-------|
| 142S | 1/2" | 1.720 | 0.700 | 0.550 | 0.312 | 100 | 1000 | 2 | 81427 |
| 143S | 3/4" | 1.980 | 0.975 | 0.630 | 0.312 | 100 | 1000 | 3 | 81437 |
| 144S | 1" | 2.210 | 1.090 | 0.750 | 0.312 | 50 | 500 | 4 | 81447 |
| 145S | 1-1/4" | 2.880 | 1.540 | 0.880 | 0.355 | 50 | 500 | 10 | 81457 |
| 146S | 1-1/2" | 3.140 | 1.750 | 0.990 | 0.335 | - | 50 | 16 | 81467 |
| 147S | 2" | 3.890 | 2.150 | 1.110 | 0.450 | - | 50 | 22 | 81477 |
| 158S | 2-1/2" | 4.925 | 2.825 | 1.245 | 0.550 | - | 25 | 62 | 81587 |
| 159S | 3" | 5.540 | 3.430 | 1.250 | 0.550 | - | 25 | 76 | 81597 |
| 160S | 3-1/2" | 6.260 | 3.900 | 1.250 | 0.575 | - | 10 | 120 | 81607 |
| 161S | 4" | 6.830 | 4.390 | 1.240 | 0.575 | - | 10 | 125 | 81613 |

APPLICATION

Snap-on type two-hole straps for E.M.T. are used where higher load bearing supports are desired.

STANDARD MATERIALS


Steel

STANDARD FINISH

Zinc Plated



Two-Hole



TYPE 2143S

| CATALOG NUMBER | TRADE SIZE | DIM A | DIM B | DIM C | DIM D | UNIT PACK | MASTER PACK | LBS. / 100 PCS. | UPC # |
|----------------|------------|-------|-------|-------|-------|-----------|-------------|-----------------|-------|
| 2142S | 1/2" | 2.200 | 0.790 | 0.560 | 0.200 | - | 250 | 1 | 21427 |
| 2143S | 3/4" | 2.700 | 0.980 | 0.620 | 0.200 | - | 200 | 2 | 21437 |
| 2144S | 1" | 2.975 | 1.185 | 0.690 | 0.200 | - | 100 | 4 | 21447 |
| 2145S | 1-1/4" | 3.650 | 1.535 | 0.750 | 0.275 | - | 50 | 5 | 21457 |
| 2146S | 1-1/2" | 4.250 | 1.765 | 0.870 | 0.275 | - | 50 | 8 | 21467 |
| 2147S | 2" | 4.730 | 2.300 | 0.995 | 0.325 | - | 25 | 13 | 21477 |
| 2158S | 2-1/2" | 6.025 | 2.855 | 0.985 | 0.345 | - | 25 | 20 | 21533 |
| 2159S | 3" | 6.460 | 3.425 | 0.995 | 0.345 | - | 20 | 25 | 21597 |
| 2160S | 3-1/2" | 7.300 | 3.925 | 0.990 | 0.345 | - | 10 | 33 | 21535 |
| 2161S | 4" | 7.895 | 4.435 | 0.995 | 0.345 | - | 10 | 36 | 21617 |