

MALLEABLE IRON 45° LIQUIDTIGHT CONNECTORS

WITH ALUMINUM LUGS FOR LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT

APPLICATION

Connects conduit and terminates bonding conductor run externally across liquidtight conduit.

FEATURES


- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with Insulated throat, steel locknut, and sealing ring
- Liquidtight/Raintight/Concrete tight/Oiltight
- Suitable for grounding
- Long ferrule prevents pull-out and tight bend conduit "pop-out"
- UL Listed liquidtight flexible metal conduit fittings are suitable for use in the following Hazardous Locations under NEC 501-4(b), 502-4(a)(2); Class I, Div.2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I.

STANDARD MATERIALS

Malleable Iron/Steel Ferrule/
Aluminum Grounding Lug

STANDARD FINISH

Zinc Plated



TYPE SLT35-45ALT

All Furnished with Insulated Throats

CATALOG NUMBER	TRADE SIZE	LUG SIZE	I.D.	O.D.	DIM A	DIM B	DIM C	DIM D	DIM E	UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
SLT25-45ALT	3/8"	#4-#14	0.590	0.793	1.62	0.50	1.15	1.48	0.75	10	100	18	50024
SLT35-45ALT	1/2"	#4-#14	0.590	0.793	1.64	0.50	1.28	1.51	0.75	10	100	20	50025
SLT36-45ALT	3/4"	#4-#14	0.785	1.020	1.68	0.52	1.55	1.54	0.75	10	100	31	50026
SLT37-45ALT	1"	#4-#14	0.980	1.261	2.16	0.65	1.80	1.81	0.75	5	50	42	50027
SLT38-45ALT	1-1/4"	#4-#14	1.330	1.605	2.50	0.66	2.25	2.16	0.75	-	10	57	50028
SLT39-45ALT	1-1/2"	#4-#14	1.530	1.844	3.10	0.73	2.44	2.43	0.75	-	10	73	50029
SLT40-45ALT	2"	#4-#14	1.995	2.337	3.28	0.75	2.97	2.82	0.75	-	5	101	50030
SLT65-45ALT	2-1/2"	#1/0-#8	2.341	2.797	6.67	1.01	4.01	4.41	1.13	-	1	373	50031
SLT66-45ALT	3"	#1/0-#8	2.939	3.418	8.01	1.15	4.18	5.50	1.13	-	1	465	50032
SLT67-45ALT	3-1/2"	#3/0-#6	3.406	3.915	9.55	1.18	5.25	5.93	1.50	-	1	686	50033
SLT68-45ALT	4"	#3/0-#6	3.882	4.411	10.64	1.25	5.78	8.34	1.50	-	1	807	50034

Also available with copper lugs. See page 132.

