

MALLEABLE IRON/**MECHANICAL GALVANIZED** 90° LIQUIDTIGHT CONNECTORS

FOR LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT

APPLICATION

To secure, ground seal Liquidtight Flexible Metal conduit, to boxes and enclosures

FEATURES

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Liquidtight/Raintight/Oiltight
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- UL Listed liquidtight flexible metal conduit fittings are suitable for use in the following Hazardous Locations under NEC 501-4(b), 502-4(a)(2); Class I, Div.2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I

STANDARD MATERIALS


Malleable Iron/Steel Ferrule

STANDARD FINISH

Sizes 1/2" - 2" - Mechanical Galvanized
 Sizes 2 1/2" - 4" - Hot Dipped Galvanized



New Product



TYPE SLT35TMG

All Furnished with Insulated Throats

| CATALOG NUMBER | TRADE SIZE | KO SIZE | I.D. | O.D. | DIM A | DIM B | DIM C | DIM D | UNIT PACK | MASTER PACK | LBS./100 PCS. | UPC # |
|----------------|------------|---------|-------|-------|-------|-------|-------|-------|-----------|-------------|---------------|-------|
| SLT35TMG | 1/2" | 1/2" | 0.590 | 0.793 | 1.43 | 0.50 | 1.28 | 1.37 | 10 | 100 | 31 | 16405 |
| SLT36TMG | 3/4" | 3/4" | 0.785 | 1.020 | 1.62 | 0.52 | 1.55 | 1.50 | 10 | 100 | 46 | 16410 |
| SLT37TMG | 1" | 1" | 0.980 | 1.261 | 1.93 | 0.65 | 1.80 | 1.81 | 5 | 50 | 77 | 16415 |
| SLT38TMG | 1-1/4" | 1-1/4" | 1.330 | 1.605 | 2.37 | 0.66 | 2.25 | 1.94 | - | 10 | 98 | 16420 |
| SLT39TMG | 1-1/2" | 1-1/2" | 1.530 | 1.844 | 2.68 | 0.73 | 2.44 | 2.40 | - | 10 | 124 | 16425 |
| SLT40TMG | 2" | 2" | 1.995 | 2.337 | 3.18 | 0.75 | 2.97 | 2.64 | - | 5 | 179 | 16430 |
| *SLT65TG | 2-1/2" | 2-1/2" | 2.341 | 2.797 | 8.31 | 1.01 | 4.01 | 7.81 | - | 1 | 847 | 16435 |
| *SLT66TG | 3" | 3" | 2.939 | 3.418 | 9.80 | 1.15 | 4.18 | 9.15 | - | 1 | 1243 | 16440 |
| *SLT67TG | 3-1/2" | 3-1/2" | 3.406 | 3.915 | 11.18 | 1.18 | 5.25 | 11.22 | - | 1 | 1914 | 16445 |
| *SLT68TG | 4" | 4" | 3.882 | 4.411 | 12.98 | 1.25 | 5.78 | 12.54 | - | 1 | 2399 | 16450 |

*Hot Dipped Galvanized

