

# ZINC CABLE AND CONDUIT CONNECTORS

FOR ARMORED CABLE, METAL CLAD AND FLEXIBLE METALLIC CONDUIT

## APPLICATION

For use with flexible metal conduit and reduced wall flexible metal conduit, metal clad and armored cable. They are used to connect two, Trade Size 3/8 (12) flexible metal conduits, two armored cable of appropriate size marked, or two metal clad cable of appropriate size marked to an enclosure through a Trade Size 1/2 (16) knockout.

## FEATURES

- UL Listed Locknut
- Male hub NPS
- Tri-combo head screws

## STANDARD MATERIALS

Zinc Die Cast




**UL LISTED**  
E198258  
CSA File No. LR57925



\*Please see Cable Chart for Cable Connectors on page 158.

## Duplex Single Screw-Clamp Type



## TYPE C270A

CATALOG NUMBER	TRADE SIZE	DIM. A MIN.	DIM. A MAX.	DIM B	UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
C270A	3/8"	0.438	1.688	1.625	25	250	13	52712

## APPLICATION

Strap-type fitting used to connect flexible metal conduit or armored cable to box or enclosure.

## FEATURES

- UL Listed Locknut
- Male Hub NPS
- Tri-combo head screws

## STANDARD MATERIALS


Zinc Die Cast



**UL LISTED**  
E198258  
CSA File No. LR57925



## Duplex Two-Screw Clamp Type



## TYPE C270

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
C270	3/8"	1.688	0.438	1.625	20	200	12	52702