

ZINC CABLE AND CONDUIT CONNECTORS

FOR ARMORED CABLE, METAL CLAD AND FLEXIBLE METALLIC CONDUIT

APPLICATION

To terminate armored cable in a 1/2" knockout in a dry location box or enclosure.

FEATURES

- Furnished with die cast locknuts
- Tri-combo head screws

STANDARD MATERIALS



Zinc Die Cast



UL LISTED
E309514
CSA File No. LR57925



Saddle Type



TYPE C920

CATALOG NUMBER	TRADE SIZE	DIM. A MIN.	DIM. B MAX	DIM B	UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
C920	3/8"	0.12	0.63	0.98	50	500	8	13512

*Please see Cable Chart for Cable Connectors on page 158.

COMBINATION COUPLINGS

FOR FLEX METAL CONDUIT TO RIGID OR IMC CONDUIT

APPLICATION

To connect Flexible metal conduit to Rigid or IMC conduit.

FEATURES

- Rigid Conduit to Flex
- Female Hub Threads - NPTt

STANDARD MATERIALS

Malleable Iron


THIRD PARTY CERTIFICATION

STANDARD FINISH:

Zinc Plated



UL LISTED
E198258



TYPE 22E

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
22E	1/2"	1.19	1.50	1.69	25	250	14	55221
23E	3/4"	1.38	1.75	1.88	20	200	19	55231
24E	1"	1.63	1.81	2.31	20	100	32	55241
25E	1-1/4"	2.00	2.31	2.62	-	20	36	55251