

# ZINC CABLE AND CONDUIT FITTINGS

## FOR NON-METALLIC SHEATHED CABLE

### APPLICATION

Used to join 1/2" steel EMT to 12-2 non-metallic sheath cable.

### FEATURES

- Assembled with tri-combo screws

### STANDARD MATERIALS


Zinc Die Cast



**UL LISTED**  
E198258



### Combination Couplings



## TYPE 170C

| CATALOG NUMBER | TRADE SIZE              | DIM A | DIM B | UNIT PACK | MASTER PACK | LBS. / 100 PCS. | UPC # |
|----------------|-------------------------|-------|-------|-----------|-------------|-----------------|-------|
| <b>*170C</b>   | 1/2" E.M.T. - 3/8" Flex | 1.28  | 1.14  | 50        | 500         | 8               | 51702 |

\* EMT to NM Cable

### APPLICATION

Used to connect underground feeder cables to enclosures in wet locations.

### FEATURES

- Assembled with a rubber grommet and steel washer

### STANDARD MATERIALS


Zinc Die Cast



**UL LISTED**  
E198258



### Underground Feeder Connectors (UF) For Service Entrance Cable and Non-Metallic Sheathed Cable



## TYPE UF10

| CATALOG NUMBER | TRADE SIZE | TYPE | MINIMUM WIRE SIZE |       | MAX. WIRE SIZE GROM. OPENING |       | UNIT PACK | MASTER PACK | LBS. / 100 PCS. | UPC # |
|----------------|------------|------|-------------------|-------|------------------------------|-------|-----------|-------------|-----------------|-------|
|                |            |      | A                 | B     | A                            | B     |           |             |                 |       |
| <b>UF10</b>    | 1/2"       | 12-2 | 0.100             | 0.475 | 0.220                        | 0.440 | 25        | 250         | 17              | 49899 |
| <b>UF20</b>    | 3/4"       | 12-3 | 0.175             | 0.800 | 0.220                        | 0.660 | 25        | 250         | 26              | 49900 |