

ZINC WATERTIGHT CONNECTORS

FOR SERVICE ENTRANCE CABLE

APPLICATION

Used to connect service entrance cable to a service enclosure in wet locations.

FEATURES

- 2 Insulating Connectors, 1 Bare
- U-Flat Style
- Assembled with rubber grommet and steel washer

STANDARD MATERIALS


Zinc Die Cast

STANDARD FINISH

Zinc Die Cast



UL LISTED
E198257



TYPE 1069C

CATALOG NUMBER	TRADE SIZE	WIRE SIZE	MINIMUM WIRE SIZE		MAX. WIRE SIZE GROM OPENING		UNIT PACK	MASTER PACK	LBS./100 PCS.	UPC #
			A	B	A	B				
1060	1"	3 #6	0.310	0.585	0.460	0.715	10	100	34	13642
1060A	1"	3 #4	0.355	0.680	0.530	0.850	10	100	34	13652
1064	1-1/4"	3 #3	0.455	0.815	0.550	0.910	10	100	52	13662
1066	1-1/4"	3 #2	0.480	0.845	0.580	0.960	10	100	52	13672
1066A	1-1/4"	3 #1	0.525	0.955	0.660	1.120	10	100	52	10660
1068	1-1/2"	3 #1/0	0.555	1.095	0.705	1.195	5	50	65	13682
1068A	1-1/2"	3 #2/0	0.595	1.125	0.740	1.235	5	50	65	13683
1069	2"	3 #1/0	0.585	1.085	0.750	1.195	5	50	87	13692
1069A	2"	3 #2/0	0.635	1.165	0.740	1.235	5	50	87	13693
1069B	2"	3 #3/0	0.685	1.285	0.830	1.415	5	50	87	1369420
1069C	2"	3 #4/0	0.655	1.275	0.890	1.540	5	50	87	13695
1069D	2"	3 #4/0	0.705	1.385	0.995	1.580	5	50	87	13696