

# COMBINATION COUPLINGS

FOR FLEX METAL CONDUIT TO RIGID OR IMC CONDUIT

### APPLICATION

To connect Flexible metal conduit to Rigid or IMC conduit.

### FEATURES

- Rigid Conduit to Flex
- Female hub threads - NPT

### STANDARD MATERIALS


Malleable Iron

### STANDARD FINISH

Zinc Plated



### Combination Couplings



### TYPE 22E

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
22E	1/2"	1.19	1.50	1.69	25	250	14	55221
23E	3/4"	1.38	1.75	1.88	20	200	19	55231
24E	1"	1.63	1.81	2.31	20	100	32	55241
25E	1-1/4"	2.00	2.31	2.62	-	20	36	55251

### APPLICATION


Used as a raceway between two enclosures.

### STANDARD MATERIALS

Zinc Die Cast



### Box Spacers



### TYPE BS50

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
BS50	1/2"	1.12	0.40	0.31	50	500	8	70504
BS75	3/4"	1.12	0.40	0.31	50	500	11	70354