

MALLEABLE IRON/**HOT DIPPED GALVANIZED** 90° LIQUIDTIGHT CONNECTORS

FOR LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT

APPLICATION

To secure, ground seal Liquidtight Flexible Metal conduit, to boxes and enclosures

FEATURES


- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Liquidtight/Raintight/Oiltight
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- UL Listed liquidtight flexible metal conduit fittings are suitable for use in the following Hazardous Locations under NEC 501-4(b), 502-4(a)(2); Class I, Div.2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I

STANDARD MATERIALS

Malleable Iron/Steel Ferrule

STANDARD FINISH

Hot Dipped Galvanized/Zinc Plated



TYPE SLT35TMG

All Furnished with Insulated Throats

CATALOG NUMBER	TRADE SIZE	KO SIZE	I.D.	O.D.	DIM A	DIM B	DIM C	DIM D	UNIT PACK	MASTER PACK	LBS./100 PCS.	UPC #
SLT35TMG	1/2"	1/2"	0.590	0.793	1.43	0.50	1.28	1.37	10	100	31	16405
SLT36TMG	3/4"	3/4"	0.785	1.020	1.62	0.52	1.55	1.50	10	100	46	16410
SLT37TMG	1"	1"	0.980	1.261	1.93	0.65	1.80	1.81	5	50	77	16415
SLT38TMG	1-1/4"	1-1/4"	1.330	1.605	2.37	0.66	2.25	1.94	-	10	98	16420
SLT39TMG	1-1/2"	1-1/2"	1.530	1.844	2.68	0.73	2.44	2.40	-	10	124	16425
SLT40TMG	2"	2"	1.995	2.337	3.18	0.75	2.97	2.64	-	5	179	16430
SLT65TG	2-1/2"	2-1/2"	2.341	2.797	8.31	1.01	4.01	7.81	-	1	847	16435
SLT66TG	3"	3"	2.939	3.418	9.80	1.15	4.18	9.15	-	1	1243	16440
SLT67TG	3-1/2"	3-1/2"	3.406	3.915	11.18	1.18	5.25	11.22	-	1	1914	16445
SLT68TG	4"	4"	3.882	4.411	12.98	1.25	5.78	12.54	-	1	2399	16450

