

# MALLEABLE IRON/**HOT DIPPED GALVANIZED** 90° LIQUIDTIGHT CONNECTORS

WITH COPPER LUGS FOR LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT

## APPLICATION

Connects conduit and terminates bonding conductor run externally across liquidtight conduit.

## FEATURES

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with Insulated throat, steel locknut, and sealing ring
- Liquidtight/Raintight/Oiltight
- Suitable for grounding and wet locations
- Long ferrule prevents pullout and tight bend conduit 'pop-out'
- UL Listed liquidtight flexible metal conduit fittings are suitable for use in the following Hazardous Locations under NEC 501-4(b), 502-4(a)(2); Class I, Div.2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I

## STANDARD MATERIALS

Malleable Iron/Steel Ferrule/Copper Grounding Lug

## STANDARD FINISH

Hot Dipped Galvanized/Zinc Plated



**TYPE SLT35CLTMG**

### All Furnished with Insulated Throats

| CATALOG NUMBER | TRADE SIZE | LUG SIZE | I.D.  | O.D.  | DIM A | DIM B | DIM C | DIM D | DIM E | UNIT PACK | MASTER PACK | LBS. / 100 PCS. | UPC # |
|----------------|------------|----------|-------|-------|-------|-------|-------|-------|-------|-----------|-------------|-----------------|-------|
| SLT35CLTMG     | 1/2"       | #4-#14   | 0.590 | 0.793 | 1.43  | 0.50  | 1.28  | 1.37  | 0.75  | 10        | 100         | 20              | 16405 |
| SLT36CLTMG     | 3/4"       | #4-#14   | 0.785 | 1.020 | 1.62  | 0.52  | 1.55  | 1.50  | 0.75  | 10        | 100         | 31              | 16410 |
| SLT37CLTMG     | 1"         | #4-#14   | 0.980 | 1.261 | 1.93  | 0.65  | 1.80  | 1.81  | 0.75  | 5         | 50          | 42              | 16415 |
| SLT38CLTMG     | 1-1/4"     | #4-#14   | 1.330 | 1.605 | 2.37  | 0.66  | 2.25  | 1.94  | 0.75  | -         | 10          | 57              | 16420 |
| SLT39CLTMG     | 1-1/2"     | #4-#14   | 1.530 | 1.844 | 2.68  | 0.73  | 2.44  | 2.40  | 0.75  | -         | 10          | 73              | 16425 |
| SLT40CLTMG     | 2"         | #4-#14   | 1.995 | 2.337 | 3.18  | 0.75  | 2.97  | 2.64  | 0.75  | -         | 5           | 101             | 16430 |
| SLT65CLTG      | 2-1/2"     | #1/0-#8  | 2.341 | 2.797 | 8.31  | 1.01  | 4.01  | 7.81  | 1.13  | -         | 1           | 373             | 16435 |
| SLT66CLTG      | 3"         | #1/0-#8  | 2.939 | 3.418 | 9.80  | 1.15  | 4.18  | 9.15  | 1.13  | -         | 1           | 465             | 16440 |
| SLT67CLTG      | 3-1/2"     | #3/0-#6  | 3.406 | 3.915 | 11.18 | 1.18  | 5.25  | 11.22 | 1.50  | -         | 1           | 686             | 16445 |
| SLT68CLTG      | 4"         | #3/0-#6  | 3.882 | 4.411 | 12.93 | 1.25  | 5.78  | 12.54 | 1.50  | -         | 1           | 807             | 16450 |

